## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 29 January 2004 (29.01.2004)

**PCT** 

## (10) International Publication Number WO 2004/008963 A1

(51) International Patent Classification<sup>7</sup>: G02B 6/16, G01N 21/47

A61B 5/103,

(21) International Application Number:

PCT/GB2003/003256

(22) International Filing Date:

23 July 2003 (23.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

02255134.5

23 July 2002 (23.07.2002) EP

(71) Applicant (for all designated States except US): ASTON PHOTONIC TECHNOLOGIES LTD [GB/GB]; Faraday Wharf, Holt Street, Birmingham B7 4BB (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ALLSOP, Thomas,


David, Paul [GB/GB]; C/o Electronic Engineering, Aston University, Aston Triangle, Birmingham B4 7ET (GB). EARTHROWL-GOULD, Timothy [GB/GB]; C/o Aston University, Aston Triangle, Birmingham B4 7ET (GB). BENNION, Ian [GB/GB]; C/o Aston University, Aston Triangle, Birmingham B4 7ET (GB).

- (74) Agent: CHAPMAN, Helga, Claire; Renshaw Barns, Upper Woodford, Salisbury, SP4 6FA (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: OPTICAL WAVEGUIDE BASED SURFACE PROFILING APPARATUS

5



(57) Abstract: Surface profiling apparatus (10) according to one embodiment comprises three long period gratings (LPGs) (12, 14, 16) fabricated in progressive three layered (PTL) fibre (18) and embedded within a deformable carrier member (40) comprising a skeleton (42) provided between two sheets of flexible rubber skin (44, 46). The LPGs (12, 14, 16) are illuminated by three wavelength modulated, bandwidth optical signals, each having a different wavelength and modulation frequency. photodetector (26) connected to three lock-in amplifiers (28, 30, 32) measures the amplitudes of the first and second harmonic frequency components of the photodetector output signal corresponding to each LPG (12, 14, 16). Similar surface profiling apparatus (10) forms the basis for respiratory function monitoring apparatus (100) in which five LPGs are provided within each of four PTL fibres (104, 106, 108, 110) and embedded in four carrier members (40a-d) attached to a garment (114) to be worn by a subject.

WO 2004/008963 A1